

Stainless steel switch gear cabinets KSS



- Switch gear cabinets with hinged door
- Mounting plate attachment above stud bolts / threaded weld nuts
- Surface grinded all sides (240 grain)
- Optional individual sizes and versions from 25 pcs (see p. 31/32)

Included in delivery:

Enclosure with door, double ward lock,
1 x M6 threaded stud bolts in lid and
4 x M6 threaded weld nuts in base.

Technical data

Material:

stainless steel 1.25 mm or 1.5 mm; 1.4301 / 304

Ingress protection:

IP 66 to EN 60529

Seal:

VMQ (silicone)

EMC on request

Surface:

grinded, grain 240

Temperature range:

-40°C to +80°C

other temperature ranges on request

Stainless steel switch gear cabinets KSS

Programme range

Order No.	Weight (g)	Mounting plates	Number of locks	Dimensions (mm)					
				A	B	C	S	H _b	H _{tot}
37.01 23 15	3500	37.01 99 01	1	200	300	25	1,25	133	155
37.01 34 21	6000	37.01 99 02	1	300	380	25	1,25	188	210
37.01 43 15	5500	37.01 99 03	1	400	300	25	1,25	133	155
37.01 46 21	11500	37.01 99 04	2	380	600	25	1,5	188	210
37.01 55 21	10500	37.01 99 05	2	500	500	25	1,25	188	210
37.01 64 15	10500	37.01 99 06	1	600	400	25	1,5	133	155
37.01 68 21	19500	37.01 99 07	4	600	760	25	1,5	188	210
37.01 99 00		Special size							

